


TRACK LIGHT

SERIES KTL 350 A/B/C




KTL-350A 12W




Parameter	Value
Model	KTL350A12WW/B
Rate Power	12W
Luminous Flux	1,080lm
Luminous Efficiency	90lm/W
Color Temperature	CCT 3000K/ 4000K/6000K
Input Voltage	AC 185-260V , 50/60Hz
Beam Angle	15° / 24° / 36°
Dimensions	73*95 mm

KTL-350B 20W



Parameter	Value
Model	KTL350B20WW/B
Rate Power	20W
Luminous Flux	1,800lm
Luminous Efficiency	90lm/W
Color Temperature	CCT 3000K/ 4000K/6000K
Input Voltage	AC 185-260V , 50/60Hz
Beam Angle	15° / 24° / 36°
Dimensions	88*115 mm

KTL-350C 30W



Parameter	Value
Model	KTL350C30WW/B
Rate Power	30W
Luminous Flux	2,700lm
Luminous Efficiency	90lm/W
Color Temperature	CCT 3000K/ 4000K/6000K
Input Voltage	AC 185-260V , 50/60Hz
Beam Angle	15° / 24° / 36°
Dimensions	105*128 mm

KTL-01 = DIMMABLE
KTL-02 = NON-DIM

