

# HIGH MAST LIGHT




## SERIES KHM SQUARE 250W-1800W

- ◆ High performance design with multi-chip package 3535/5050 LED source and exclusive Lens increase performance, low light failure and dead lights. The light transmittance up to 98%. Luminous efficacy up to 110-130lm/w. 10°/15°/24°/36°/60°/90°/30X45°/40X90° for option, Uniform light distribution apply to different industrial light projects.
- ◆ Excellent operating temperature -40°C ~ 50°C
- ◆ High pressure die-cast aluminum alloy housing.
- ◆ Made of non-corrosion heat sink with electrophoresis process technology.
- ◆ -180° ~ 180° adjustable angle available for outdoor & indoor lighting application.
- ◆ Green product, no UV, IR radiation or mercury pollution. IEC62471 passed.
- ◆ With excellent housing design reach IP66/IK10 rating.
- ◆ Installation method optional by wall mounted & pole mounted.
- ◆ Lifespan over 50,000 hours, 5 years warranty



250W-1800W



Parameter	Value								
Model	KHM250 WS	KHM300 WS	KHM500 WS	KHM600 WS	KHM900WS	KHM1000 WS	KHM1200 WS	KHM1500 WS	KHM1800 WS
Rate Power	250W	300W	500W	600W	900W	1,000W	1,200W	1,500W	1,800W
Luminous Flux	32,500lm	39,000lm	65,000lm	78,000lm	117,000lm	130,000lm	156,000lm	195,000lm	234,000lm
Luminous Efficiency	130lm/w								
Color Temperature	3000K/4000/5000K/6000K								
Color Rendering Index	> 70 Ra								
Input Voltage	AC 100-277V , 50/60Hz								
Beam Angle	10°/15° 24°/36°/60°/90°/30X45°/90X40°								
Work Temperature	-40°C to +50°C								
Work Life	>50,000 Hours								
Housing Material	Aluminum 6063-T5								
IP Rating	IP66 ,IK10								
Net Weight	5.6 kg		13.5 kg		19.5 kg		25 kg		35 kg
Dimensions (mm)	354*325*163		409*500*163		409*748*163		745*557*163		745*807*163

# HIGH MAST LIGHT


SERIES KHM SQUARE 250W-1800W




## Product Details



## IP66 Whole Lamp



## Distribution Curve



[www.kbmlighting.com](http://www.kbmlighting.com)